

# WISECO Duoline

## The Hot Wax Spray Gun



### **WISECO** Duoline The Hot Wax Spray Gun

Whether you want to apply wood with wax improve or in Injection moulding range, the employment that VISECO Duoline is just as practical as time-saving and the result always first-class.

The material which can be laid on becomes warmed up in the heatable cup and liquefies completely. The spraying nozzle is also heated and keeps the material warm until it comes out from the spray gun.

Applying is up this way also with difficulty accessible ranges very easy and the result an always absolutely even surface.

### **The Hot Wax Pressure Tank System**

This system is for the using by hand and also as a component for automated spraying lines.

The material warms up in 12 litres large tank and becomes liquid over a very compact heating hose with an inside heating also absolutely equivalent lasting temperature to the spray gun with less overspray.



# WISECO Duoline

## The Hot Wax Spray Gun

### Application possibilities

Working with the VISECO duo LINE hot wax spray gun is possible with each application, with which solvent-free media are to be liquefied by heating up. The hot wax technology worked satisfactorily for example

- during the refinement of wood surfaces with wax
- when applying within the injection moulding range
- to impregnate packing materials
- when applying viscous lubricants, e.g. for the corrosion protection
- with the model and building of forms
- with improving and designing of candles and wax sculptures
- within the professional ski service range

### Advantages

- improved results for the surface refinement
- simple function
- careful material heating up
- small air consumption

### Technical Data of the hot wax spray gun

Weight	1300 g
Mains voltage	230 VAC
Output voltage	40 VDC
Power	250 VA
Classification	IP 54
Temperature	20° - 95°C
Atomizing pressure	receive about 0,8 bar
Max. filling amount flow cup	0,4 l
Max. filling amount cartridge	310 ml

### Technical Data of the hot wax pressure tank

Mains voltage	230 VAC
Classification	IP 64
Temperature	60° - 95°C
Material pressure	adjustably 0 - 3 bar
Max. filling amount tank	about 12 l
Measures (BxHxD)	40 x 60 x 40 cm



furniture improve with hot wax - very easy



high-quality wood surfaces - by nature beautifully



wood surface refinement with the Duoline hot wax spray gun



parquet finish with hot wax



for working outside of the workshop we recommend the practical cartridge system